

SLC – 2.5" PATA SLC SSD Drive PRODUCT SPECIFICATIONS:

System Performance

SLC – NAND Flash : 44 pin PATA IDE

Data Transfer Mode PIO Mode0-4, MWDMA 0-2, UDMA Mode 0-4

Sequential Read 36.4MB / sec Max.

Sequential Write 26.5MB / sec Max.

Average Access Time 0.2ms (estimated)

Environmental Specification

Standard Temperature Operation 0°C ~ +70°C

Non-operation -20°C ~ +80°C

Wide Temperature Operation -40°C ~ +85°C

Non-operation -50°C ~ +95°C

Vibration Operation max 15G compliant to MIL-STD-810F

Shock Operation max 1500 G compliant to MIL-STD-810F

Humidity Operation max 10~95% non-condensing

Altitude 70,000 Feet

Reliability

Main Time Between Failure > 3,000,000 hours

Wear Leveling Static Algorithms

Error Code Correction 4 bits per 512 byte blocks

Endurance > 2,000,000 cycles

Data Retention 10 years

Power Consumption

Power Voltage 5V ± 10%

Reading mode 124mA (Max)

Writing mode 121mA (Max)

Sleep Mode 1.8mA (Max)

Physical Specifications

Length 99.70 mm

Width 69.90 mm

Thickness 9.50 mm

Weight 110.0 g (3.88 oz)

Irvine, California 92618 USA

TEL: +1 714-881-4777 FAX: +1 801-847-8644

E-Mail: sales@PCcardsDirect.com